



Industrial Monitor

15" Open Frame Monitor

15"

16M

250 cd/m²



Display	
Display Type	15" XGA TFT LCD
Resolution	1024 (H) x 768 (V)
Pixel Pitch	0.297 (H) x 0.297 (V) (mm)
Display Color	16M
Brightness	250 cd/m ²
Contrast Ratio	450:1
Viewing Angle	L/R:-70° ~ +70°, U/D:-60° ~ +65°
Response Time	16 (Tr+Tf) (ms)
Back Light MTBF	50,000 (hour)
Construction	Heavy duty steel chassis with VESA 75/100mm standard screw holes
OS Support	MS DOS, Windows 98/SE, Windows NT4.0, Windows 2000, Windows XP
Menu OSD	Yes

Order Information	
AT-OP15	15" Open Frame
AT-OP15TS	15" Open Frame with Touchscreen, RS232
AT-OP15TU	15" Open Frame with Touchscreen, USB
Option	
AT-OP-EXAV	AV Connector instead serie
AT-OP-EXDVI	DVI instead serie

I/O	
Power Input	External 48WDC 12V power adapter
Audio input	Line-in
Video input	15 pin D-SUB, AV input (Optional)

Touch Screen	
Type	Five-wire Analog resistive
Controller	RS-232 (AT-OP15TS) USB (AT-OP15TU)
Resolution	continuous
Light transmission	79%or more
Power consumption	<5V @100Ma

Mechanical and Environmental	
Operating temperature	10 °C~ 45°C(32°F~ 113°F)
Storage temperature	-20°C~60°C(-4°F~ 140°F)
Storage humidity	20% ~ 80%
Dimensions	378 x 295 x 50mm
Gross Weight	6.5 (kg)

DRAWING

