


ADP-1XX6 Series

Stainless Steel Display



Features



Stainless Steel,
Sturdy and Reliable



Rear OSD



IP 65 Except I/O Side



Flexible Optional I/O



Wide Range DC 11~32V
Power Input

ADP-1XX6 Series

ADP-1156/ADP-1176/ADP-1196

External I/O Port



ADP-1176



ADP-1156



ADP-1196

ADP-1156/ADP-1176/ADP-1196

Default:

- 1 x VGA input
- 1 x DC power input

Optional:

- DVI, S-Video, Touch I/O, DC 12V input

Display

ADP-1XX6 Series

Stainless Steel Display

Specifications

Model No.	ADP-1156	ADP-1176	ADP-1196
LCD			
Display Type	15" TFT- LCD	17" TFT- LCD	19" TFT- LCD
Max. Resolution	1024x768	1280x1024	1280x1024
Max. Color	262K	262K	16.7M
Luminance (cd/m ²)	350	300	300
View Angle	H:150° / V:140°	H:140° / V:130°	H:160° / V:160°
Backlight Lifetime	50,000 hrs	40,000 hrs	20,000 hrs
System			
Input Signal	RGB		
On Screen Display Control	On the rear side		
External I/O Port	Default: • 1 x VGA input • 1 x DC power input Optional: • DVI, S-Video, Touch I/O, DC 12V input		
Power Supply			
Power Input	DC 11~32V		
Touch Screen			
Type	Resistive (optional)		
Mechanical			
Construction	Stainless Steel Enclosure		
IP Rating	IP 65 except I/O side		
Mounting	VESA 75x75 Mount	VESA 75x75 Mount	VESA 100x100 Mount
Dimension	398(W)x316(H)x53(D) mm	432(W)x358(H)x57.4(D) mm	470(W)x388.6(H)x60(D) mm
Net Weight	5.74kgs	7kgs	8kgs
Environmental			
Operating Temperature	0~50 °C		
Storage Temperature	-20~60 °C		
Storage Humidity	10~90% @40 °C non-condensing		
Certificate	CE/FCC Class A		

Ordering Information

Model	Description
ADP-1156T-09	15" XGA 1024 x 768 5 sides IP65 display ,VGA input, OSD on the back side, resistive touch USB interface,11~32V DC input with adaptor, stainless steel enclosure
ADP-1156T-08	15" XGA 1024 x 768 5 sides IP65 display ,VGA/DVI/S-Video input, OSD on the back side, resistive touch USB interface,11~32V DC input with adaptor, stainless steel enclosure
ADP-1156-02	15" XGA 1024 x 768 5 sides IP65 display ,VGA input, OSD on the back side, no touch, 11~32V DC input with adaptor, stainless steel enclosure
ADP-1176T-04	17" SXGA 1280 x 1024 5 sides IP65 display ,VGA input, OSD on the back side, resistive touch USB interface,11~32V DC input with adaptor, stainless steel enclosure
ADP-1176T-08	17" SXGA 1280 x 1024 5 sides IP65 display ,VGA/DVI/S-Video input, OSD on the back side, resistive touch USB interface,11~32V DC input with adaptor, stainless steel enclosure
ADP-1196T-02	19" SXGA 1280 x 1024 5 sides IP65 display ,VGA input, OSD on the back side, resistive touch USB interface,11~32V DC input with adaptor, stainless steel enclosure
ADP-1196T-04	19" SXGA 1280 x 1024 5 sides IP65 display ,VGA/DVI/S-Video input, OSD on the back side, resistive touch USB interface,11~32V DC input with adaptor, stainless steel enclosure
ADP-1196-01	19" SXGA 1280 x 1024 5 sides IP65 display ,VGA input, OSD on the back side, no touch ,11~32V DC input with adaptor, stainless steel enclosure

ADP-1XX6 Series

ADP-1156/ADP-1176/ADP-1196

Dimensions

unit:mm

